



SMALL FOOTPRINT.
ELEGANT LINES.



I SERIES

(formerly Teledex iPhone™)

Accept no substitutes.



I Series VoIP

- Single or Two line speakerphones
- VoIP-based protocol; SIP RFC 3261 compliant
- Codecs supported: G711a; G711µ; G729
- Corded Supports 802.1Q VLAN tagging
- 2-port 10/100 ethernet switch
- Supports 802.1Q VLAN tagging
- Supports DHCP or static IP address
- Electronic 3-way conference*; Hold, Mute, Redial keys
- Cordless: Supports up to five handsets, including one on the base and four remotes (RediDock kits); AutoSync – handset automatically syncs with base unit when in cradle
- 5 or 10 Configurable Guest Service Keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Corded: Visual message waiting indicator
- Cordless: Bright message waiting indicator and positive charge indicator
- Cordless: Optional remote cordless handset battery backup

*Two-line only

I Series Cordless Series Analog

- Single or Two line speakerphones
- OneTouch voice mail access
- Electronic 3-way conference*
- Cordless: PrimeLine/RingLine™ automatic line selection*
- 5 or 10 Configurable Guest Service Keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Corded: Flash, Hold, Mute, Conference*, Redial keys; Bright message waiting indicator; Desk or wall mountable

*Two-line only

I Series Trimline Analog

- Single or Two line configuration
- Optional message waiting indicator; Flash, Redial, Mute keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Analog data port

*Two-line only

I SERIES VoIP

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.125" (5.40cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.375" (8.57cm) (d) (with handset)
Footprint (Wall):	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.0" (5.08cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.5" (8.89cm) (d) (with handset)
Footprint (RediDock, Cordless) (Desk, Wall):	2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 2.25" (5.72cm) (d) (without handset); 2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 3.38" (8.59cm) (d) (with handset)
Weight:	1.8 lbs. (0.81kg)
Weight (Redidock, Cordless):	7 oz. (0.2kg) (without handset); 0.8 lbs. (0.36kg) (with handset)
Frequency:	1.9 GHz or 1.8 GHz
Power:	Power over Ethernet (PoE)
Standby Time (Cordless):	14 days

Talk Time (Cordless):	4 hours
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock, Cordless):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	Meets or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard:	ETL and CE
Operating Voltage:	24 to 56 VDC Non-Polarity
Flash Timing:	600 ms
Ringer Equivalence:	Z (Use only behind PBX)
Registered Connector (Corded):	USOC RJ-14
Handset:	Hearing Aid compatible
Line Cord (Cordless):	12-foot, 2 RJ45
Cords & Line (Corded):	12-foot RJ45/10-foot coil

PART NUMBERS

SINGLE-LINE VoIP 1.9 GHz CORDLESS

NDC2105s (5-button speaker)

IPN96459IP-N	Ash
IPN964591IP-N	Black

NDC2110s (10-button speaker)

IPN96559IP-N	Ash
IPN965591IP-N	Black

RediDock 1.9 GHz (Single-line)

IRD9110-POE

IPN96559IPHDKIT-N	Ash
IPN965591IPHDKIT-N	Black

TWO-LINE VoIP 1.9 GHz CORDLESS

NDC2205s (5-button speaker)

IPN98459IP-N	Ash
IPN984591IP-N	Black

NDC2210s (10-button speaker)

IPN98559IP-N	Ash
IPN985591IP-N	Black

RediDock 1.9 GHz (Two-line)

IRD9210-POE

IPN98559IPHDKIT-N	Ash
IPN985591IPHDKIT-N	Black

SINGLE-LINE VoIP 1.8 GHz CORDLESS

NDC2105S (5-button speaker)

IPN96259IP-N	Ash
IPN962591IP-N	Black

NDC2110S (10-button speaker)

IPN96359IP-N	Ash
IPN963591IP-N	Black

RediDock 1.8 GHz (Single-line)

IRD8110-POE

IPN96359IPHDKIT-N	Ash
IPN963591IPHDKIT-N	Black

TWO-LINE VoIP 1.8 GHz CORDLESS

NDC2205S (5-button speaker)

IPN98259IP-N	Ash
IPN982591IP-N	Black

NDC2210S (10-button speaker)

IPN98359IP-N	Ash
IPN983591IP-N	Black

RediDock 1.8 GHz (Two-line)

IRD8210-POE

IPN98539IPHDKIT-N	Ash
IPN985391IPHDKIT-N	Black

SINGLE-LINE VoIP CORDED

ND2105s (5-button speaker)

IPN33149IP-N	Ash
IPN331491IP-N	Black

ND2110s (10-button speaker)

IPN333349IP-N	Ash
IPN3333491IP-N	Black

TWO-LINE VoIP CORDED

ND2205s (5-button speaker)

IPN34149IP-N	Ash
IPN341491IP-N	Black

ND2210s (10-button speaker)

IPN34359IP-N	Ash
IPN343591IP-N	Black



I SERIES TRIMLINE ANALOG

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint:	2.75" (w) x 8.25" (l) x 3.38" (d) [6.99cm x 20.96cm x 8.59cm]
Weight:	0.8 lbs. (0.36kg)
Power:	Line
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	20 per carton

PART NUMBERS

I Series Trimline (Single-line)

AT1101 NO/MW	AT1102 W/MW
IPN33019	IPN33119
IPN330191	IPN331191

FCC Specifications:	Meets or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard:	ETL and CE
Operating Voltage:	24 to 56 VDC Non-Polarity
Ringer Equivalence:	Z (Use only behind PBX)
Registered Connector:	USOC RJ-14
Handset:	Hearing Aid compatible
Cords & Line:	10-foot coil/8 -inch line cord

I Series Trimline 2 (Two-line)

AT1201 NO/MW	AT1202 W/MW
IPN34059	IPN34159
IPN340591	IPN341591

I SERIES ANALOG

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.125" (5.40cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.375" (8.57cm) (d) (with handset)
Footprint (Wall):	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.0" (5.08cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.5" (8.89cm) (d) (with handset)
Footprint (RediDock, Cordless) (Desk, Wall):	2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 2.25" (5.72cm) (d) (without handset); 2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 3.38" (8.59cm) (d) (with handset)
Weight:	1.8 lbs. (0.81kg)
Weight (Redidock, Cordless):	7 oz. (0.2kg) (without handset) 0.8 lbs. (0.38kg) (with handset)
Frequency (Cordless):	1.9 GHz or 1.8 GHz
Power:	Line
(Cordless)	12 VDC adapter

Standby Time (Cordless):	14 days
Talk Time (Cordless):	6 hours
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	Meets or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard:	ETL and CE
Operating Voltage:	24 to 56 VDC Non-Polarity
Flash Timing:	100 ms to 1000 ms
Ringer Equivalence:	Z (Use only behind PBX)
Registered Connector (Cordless):	USOC RJ-14
Handset:	Hearing Aid compatible
Line Cord (Cordless):	12-foot, 1-RJ45 and 1-RJ14
Cords & Line (Cordless):	12-foot/10-foot coil

PART NUMBERS

SINGLE-LINE ANALOG 1.9 GHz

CORDLESS

AC9105s (5-button speaker)

IPN96459	Ash
IPN964591	Black

AC9110s (10-button speaker)

IPN96559	Ash
IPN965591	Black

RediDock 1.9 GHz (Single-line)

IRD9110 Intl.

IPN96559HDKIT	Ash
IPN965591HDKIT	Black

TWO-LINE ANALOG 1.9 GHz CORDLESS

AC9205s (5-button speaker)

IPN98459	Ash
IPN984591	Black

AC9210s (10-button speaker)

IPN98559	Ash
IPN985591	Black

RediDock 1.9 GHz (Two-line)

IRD9210 Intl.

IPN98559HDKIT	Ash
IPN985591HDKIT	Black

SINGLE-LINE ANALOG 1.8 GHz

CORDLESS

AC8105s Intl. (5-button speaker)

IPN96259	Ash
IPN962591	Black

AC8110s Intl. (10-button speaker)

IPN96359	Ash
IPN963591	Black

RediDock 1.8 GHz (Single-line)

IRD8110 Intl.

IPN96359HDKIT	Ash
IPN963591HDKIT	Black

TWO-LINE ANALOG 1.8 GHz CORDLESS

AC8205s Intl. (5-button speaker)

IPN98259	Ash
IPN982591	Black

AC8210s Intl. (10-button speaker)

IPN98359	Ash
IPN983591	Black

RediDock 1.8 GHz (Single-line)

IRD8210 Intl.

IPN98359HDKIT	Ash
IPN983591HDKIT	Black

SINGLE-LINE ANALOG CORDED

A101 (Lobby)

IPN33009	Ash
IPN330091	Black

A100 (Basic)

IPN33309	Ash
IPN333091	Black

A102 (Basic)

IPN33039	Ash
IPN330391	Black

A103 (3-button)

IPN33739	Ash
IPN337391	Black

A105 (5-button)

IPN33139	Ash
IPN331391	Black

A110 (10-button)

IPN33239	Ash
IPN332391	Black

A100s (Basic speaker)

IPN33049	Ash
IPN330491	Black

A103s (3-button speaker)

IPN33749	Ash
IPN337491	Black

A105s (5-button speaker)

IPN33149	Ash
IPN331491	Black

A110s (10-button speaker)

IPN33339	Ash
IPN333391	Black

TWO-LINE ANALOG CORDED

A200s (Basic speaker)

IPN34049	Ash
IPN340491	Black

A203s (3-button speaker)

IPN34749	Ash
IPN347491	Black

A205s (5-button speaker)

IPN34149	Ash
IPN341491	Black

A210s (10-button speaker)

IPN34359	Ash
IPN343591	Black



U.S. Toll Free 1 800 794 8353
Telephone +1 719 638 8821
Fax +1 719 638 8815

info@teledex.com
teledex.com

© 2017 Cetus, Inc. Product specifications and descriptions in this document subject to change without notice.
Cetus®, Teledex®, TeleMatrix®, and Scitec® are trademarks or registered trademarks of Cetus, Inc.

TDX-HS-122017